

MAP Polarization Controller

(mPCS-A1)



Key Features

- Complete polarization control
- Designed to meet IEEE Std. 802.3ae™ 10 GbE testing requirements
- Designed to perform fast polarization dependent loss (PDL) measurements (4-state Mueller method)
- Compact single width cassette
- Very high angular accuracy and absolute fast axis alignment accuracy
- Can be automated when used with MAP-200 LXI-compliant interfaces and IVI drivers

Applications

- Passive component PDL and polarization mode dispersion (PMD) measurements
- EDFA noise and polarization dependent gain (PDG) measurements
- 10 GbE transceiver worst-case relative intensity noise and dispersion penalty measurements
- Optical signal to noise ratio (OSNR) and extinction ratio (ER) measurements

Safety Information

- The MAP Polarization Controller, when installed in a MAP chassis, complies to CE, CSA/UL/IEC61010-1, plus LXI Class C requirements.

The Multiple Application Platform (MAP) Polarization Controller (mPCS-A1) is optimized for the industry-leading JDSU MAP-200 platform. Based on the previous-generation Multiple Application Platform (MAP), the MAP-200 is the first photonic layer lab and manufacturing platform that is LAN Extensions for Instrumentation (LXI)-compliant by conforming to the required physical attributes, Ethernet connectivity, and interchangeable virtual instrument (IVI) drivers. The MAP-200 platform is optimized for density and maximum configurability to meet specific application requirements in the smallest possible foot print.

The mPCS-A1 provides an efficient and precise way of creating any state of polarization. It can also be used as part of a polarization state analyzer. The mPCS-A1 is comprised of three rotating elements: a high extinction ratio polarizer, a quarter-wave plate and a half-wave plate. The controller configuration can be offered with a single-mode (SM) or a polarization maintaining fiber (PMF) input.

The polarization controllers can be combined with other instruments to complete measurement test systems such as erbium-doped fiber amplifier (EDFA) or passive component test sets.

Specifications

Parameter	1310 nm	1550 nm
Wavelength range	1260 to 1360 nm	1420 to 1630 nm
Insertion loss (IL) ^{1,3}	<1.5 dB	<1.5 dB
IL variation with wavelength ^{1,3}	±0.1 dB	±0.1 dB
IL variation with rotation ^{1,3,4}	±0.05 dB	±0.05 dB
Return loss (RL)	>45 dB	>45 dB
Extinction ratio ²		>40 dB
Fast axis alignment accuracy		<± 0.5°
Angular accuracy		±0.1°
Rotational resolution		0.075°
Maximum rotational speed per element		900°/s
Maximum optical input power		100 mW
Calibration		2 years
Operating temperature		10 to 40°C
Storage temperature		-30 to 60°C
Humidity	Maximum 95% RH from 10 to 40°C non-condensing	
Dimensions (W x H x D)	4.06 x 13.26 x 37.03 cm (1.6 x 5.22 x 14.58 in)	
Weight	1.6 kg (3.5 lb)	

1. From 1520 to 1630 nm for the 1550 nm version
2. Measured with a >45 dB polarized narrow spectral line source
3. At 23°C ±5°C
4. IL variation using an incoherent (broadband) source with both waveplates rotating at differing rates

Ordering Information

For more information on this or other products and their availability, please contact your local JDSU account manager or JDSU directly at 1-800-498-JDSU (5378) in North America and +800-5378-JDSU worldwide or via e-mail at customer.service@jdsu.com.

Product Code	Description
Base Options (Required, select one)	
MPCS-A1300	Polarization controller, 1260 to 1360 nm
MPCS-A1500	Polarization controller, 1420 to 1630 nm
Fiber Type Options (Required, select one)	
M100	9/125 fiber type
M103	PMF fiber type
Connector Options (Required, select one)	
MFP	FC/PC connector type
MFA	FC/APC connector type
MSC	SC/PC connector type
MSU	SC/APC connector type

UL is a registered trademark of Underwriters Laboratories Inc.
 IEEE Std.802.3ae is a registered trademark of the Institute of Electrical and Electronics Engineers

Test & Measurement Regional Sales

NORTH AMERICA TOLL FREE: 1 866 228 3762 FAX: +1 301 353 9216	LATIN AMERICA TEL: +55 11 5503 3800 FAX: +55 11 5505 1598	ASIA PACIFIC TEL: +852 2892 0990 FAX: +852 2892 0770	EMEA TEL: +49 7121 86 2222 FAX: +49 7121 86 1222	www.jdsu.com/test
---	--	---	---	--